# 2025

SUMMIT ADRENALINE WITH EDGE PACKAGE

This high-end in-season package is loaded with proven technical features.



### // PACKAGE HIGHLIGHTS

- REV Gen5 platform
- Premium LED headlights
- Rotax® 850 E-TEC® available
- · High-quality KYB 36 shock package
- tMotion X rear suspension

- E-TEC® SHOT™ starter standard
- · Narrow deep snow running boards with large openings
- RAS™ 3 front suspension with 34 in. ski stance
- PowderMax X-Light 3 in. with FlexEdge available
- · Narrow bodywork
- · Compact and lightweight deep snow seat
- Pilot DS 3 skis
- Belt-monitoring system

ROTAX ENGINE	850 E-TEC			
Engine details	Liquid-cooled, two-stroke, eRAVE™			
Horsepower*	165			
Cylinders - Displacement	2 - 849 cc			
Bore - Stroke (mm)	82 x 80.4			
Fuel System	E-TEC® direct injection with additional booster injectors			
Fuel type – Octane	Regular unleaded - 95			
Fuel tank (L/US gal)	36 / 9.5			
Oil tank capacity (L/qt)	3.4 / 3.6			
POWERTRAIN				
Drive clutch	pDrive™ with clickers			
Driven clutch	QRS Vent Plus			
Drive sprocket pitch (mm/in.)	73 / 2.86 (146 in.)			
	89 / 3.5 (154 in.)			
DRY WEIGHT				
Dry weight (kg)	204.1 (146 in.)			
	201.9 (154 in.)			
DIMENSIONS				
Vehicle overall length (mm/in.)	3,058 / 120.4 (146 in.)			
•	3,188 / 125.5 (154 in.)			
Vehicle overall width (mm/in.)	1,024 / 40.3 (adjustable)			
Vehicle overall height (mm/in.)	1,395 / 54.9			
Ski stance (mm/in.)	864 / 34 (adjustable)			
Available tracks (in.)	PowderMax† II with FlexEdge™:			
(Length x width x profile)	146 x 16 x 2.5			
	PowderMax <sup>†</sup> X-Light with FlexEdge™:			

### COLOR

SUSPENSION	
Front suspension	RAS™ 3
Front shock	KYB 36
Front suspension travel (mm/in.)	207 / 8.2
Rear suspension	tMotion™ X
Center shock	KYB 36
Rear shock	KYB 36
Rear suspension travel (mm/in.)	264 / 10.4

## Platform Headlights Premium high-performance LED

Skis	Pilot™ DS 3
Seating	Deep snow compact
Handlebar	Tapered with J-hooks / Grab handle
Riser block height (mm/in.)	165 / 6.5
Starter	SHOT
Reverse	RER™
Brake system	Brembo
Heated throttle lever/grips	Standard
Gauge type	4.5 in. digital
Windshield	0ptional
Runner (in.) – Carbide (in.)	3/8 square / 4
Bumpers (front/rear)	Std / Std





REV® Gen5

154 X 16 X 3.0

# 2025

# SUMMIT ADRENALINE

An excellent deep-snow machine for any rider.



## // PACKAGE HIGHLIGHTS

- REV Gen5 platform
- Rotax® 850 E-TEC® and 600R E-TEC engines available
- tMotion X rear suspension
- LED headlights

- Narrow bodywork
- · High-quality KYB 36 shock package
- RAS™ 3 front suspension with 36 in. ski stance
- Narrow deep snow running boards with large openings
- Glove box with 3.5 L of storage
- Low handlebar strap
- Pilot DS 3 skis
- Belt-monitoring system

ROTAX ENGINE	850 E-TEC	600R E-TEC			
Engine details	Liquid-cooled, two-stroke, eRAVE™	Liquid-cooled, two-stroke eRAVE™			
Horsepower*	165	125			
Cylinders – Displacement	2 - 849 cc	2 - 599.4 cc			
Bore – Stroke (mm)	82 x 80.4	72.3 x 73			
Fuel System	E-TEC® direct injection with additional booster injectors	E-TEC® direct injection			
Fuel type – Octane	Regular unleaded - 95	Regular unleaded - 95			
Fuel tank (L/US gal)	36 / 9.5	36 / 9.5			
Oil tank capacity (L/qt)	3.4 / 3.6	3.4 / 3.6			
POWERTRAIN					
Drive clutch Driven clutch	pDrive™ with clickers QRS Vent Plus	pDrive™ with clickers QRS Vent			
Drive sprocket pitch (mm/in.)	73 / 2.86 (146 in.) 89 / 3.5 (154 in.)				
DRY WEIGHT					
Dry weight (kg)	203.7 (146 in.) 201.9 (154 in.)	196.9 (146 in.) 195 (154 in.)			
DIMENSIONS					
Vehicle overall length (mm/in.)	3,208 / 122.4 (146 in.) 3,318 / 130.6 (154 in.)				
Vehicle overall width (mm/in.)	1,073 / 42.2	1,073 / 42.2 (adjustable)			
Vehicle overall height (mm/in.)	1,395/54.9				
Ski stance (mm/in.)	930 / 36 [	930 / 36 (adjustable)			
Available tracks (in.)		with FlexEdge™:			
(Length x width x profile)	146 x 16 x 2.5				
	PowderMax <sup>†</sup> Light with FlexEdge™:				
	154 x 16 x 2.5				

CULUK	
Catalyst Grey	
SUSPENSION	
Front suspension	RAS™ 3
Front shock	KYB 36
Front suspension travel (mm/in.)	215 / 8.5
Rear suspension	tMotion™ X
Center shock	KYB 36
Rear shock	KYB 36
Rear suspension travel	264 / 10 4

FEATURES	
Platform	REV® Gen5
Headlights	High-performance LED
Skis	Pilot™ DS 3
Seating	Deep snow
Handlebar	Tapered with J-hooks / Grab handle
Riser block height (mm/in.)	165 / 6.5
Starter	Electric
Reverse	RER™
Brake system	Brembo
Heated throttle lever/grips	Standard
Gauge type	4.5 in. digital
Windshield	Optional
Runner (in.) – Carbide (in.)	3/8 square / 4
Bumpers (front/rear)	Std / Std





# 2025

# SUMMIT X WITH EXPERT PACKAGE

The ultimate precise and predictable deep-snow sled with features sharpened for most technical terrains.

## // WHAT'S NEW

- KYB Pro 36 EA-3 piggyback front shocks
- $\bullet$  10.25 in. touch screen display with BRP Connect and built-in GPS
- 2 color options



## // PACKAGE HIGHLIGHTS

- Rotax® 850 E-TEC® Turbo R and 850 E-TEC engines available
- REV Gen5 platform
- Premium LED headlights
- tMotion XT rear suspension with rigid rear arm
- PowderMax X-Light 3 in. track options with full-width rods
- Premium shock package with stiffer calibration
- Short tunnel with lightweight snowflap
- E-TEC® SHOT™ starter standard
- Narrow extruded profile running boards with extra-large openings
- · Flexible handguards
- Short riser block [120 mm / 4.7 in.]
- · Sea-level calibration

- Narrow bodywork
- · Ultra compact and lightweight deep snow seat
- · Adjustable limiter strap
- · Belt-monitoring system
- Adjustable brake lever
- Pilot DS 4 skis
- RAS™ 3 front suspension with 34 in. ski stance

ROTAX ENGINE	850 E-TEC TURBO R	850 E-TEC		
Engine details	Liquid-cooled, two-stroke, turbocharged, eRAVE™	Liquid-cooled, two-stroke, eRAVE™		
Horsepower*	180 up to 8,000 ft.	165		
Cylinders - Displacement	2 - 849 cc	2 - 849 cc		
Bore - Stroke (mm)	82 x 80.4	82 x 80.4		
Fuel System	E-TEC® direct injection with additional booster injectors	E-TEC® direct injection with additional booster injectors		
Fuel type – Octane	Regular unleaded - 95	Regular unleaded - 95		
Fuel tank (L/US gal)	36 / 9.5	36 / 9.5		
Oil tank capacity (L/qt)	3.4 / 3.6	3.4 / 3.6		

### **POWERTRAIN**

Drive clutch	pDrive™ with clickers		
Driven clutch	QRS Vent Plus		
Drive sprocket pitch (mm/in.)	89/3.5		

### DRY WEIGHT

Dry weight (kg)	207.3 (154 in.) 210 (165 in.)	198.2 (154 in.) 201.4 (165 in.)

### DIMENSIONS

venicle overall length (mm/in.)	3,188 / 125.5 (154 ln.) 3,299 / 129.9 (165 in.)		
Vehicle overall width (mm/in.)	1,024 / 40.3 (adjustable)		
Vehicle overall height (mm/in.)	1,306 / 51.4		
Ski stance (mm/in.)	864 / 34 (adjustable)		
Available tracks (in.) [Length x width x profile]	PowderMax <sup>1</sup> X-Light 154 x 16 x 3.0 165 x 16 x 3.0		

### COLOR

Dusty Navy (painted)	
Timeless Black (painted)	

S	U	<u>S</u>	<u>۲</u>	<u>E</u>	N	<u>S</u>	l	U	N	

Front suspension	RAS™ 3
Front shock	KYB Pro 36 EA-3 with lightweight springs
Front suspension travel (mm/in.)	207 / 8.2
Rear suspension	tMotion™ XT with Adjustable limiter strap
Center shock	KYB 36 Plus with lightweight spring
Rear shock	KYB Pro 36 EA-3
Rear suspension travel [mm/in.]	264 / 10.4

#### **FEATURES**

Platform	REV® Gen5
Headlights	Premium high-performance LED
Skis	Pilot™ DS 4
Seating	Deep snow ultra compact
Handlebar	Tapered with J-hooks / Grab handle / Flexible handguards
Riser block height (mm/in.)	120 / 4.7
Starter	SHOT
Reverse	RER™
Brake system	Brembo with adjustable lever
Heated throttle lever/grips	Standard
Gauge type	4.5 in. digital 10.25 in. touchscreen (opt.)
Windshield	Optional
Runner (in.) - Carbide (in.)	3/8 square / 4
Bumpers (front/rear)	Std / Std



