# **MY24 COMMANDER MAX XT 1000R**



#### **HIGHLIGHTS**

- 64 in. (162.6 cm) wide with Arched A-arm
- 7.6 in. (19.3 cm) digital display with keypadCan-Am LED signature
- 28 in. (71.1 cm) XPS Trail King tires
- 14 in. (35.6 cm) cast-aluminum wheels
- XT front bumper
- 4,500-lb (2,041 kg) winch
- Full roof

# **ENGINE**

Туре	75 kW (100 hp), Rotax® 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Selectable Turf Mode / 2WD / 4WD with Visco-Lok† auto-locking front differential
Driving Assistance	Electronic Hill Descent Control SPORT / ECO™ modes
Power Steering	Dynamic Power Steering (DPS™)

#### SUSPENSIONS

Front Suspension	Arched double A-arm with sway bar / 15 in. (38.1 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	Arched TTA with sway bar / 15 in. (38.1 cm) travel
Rear Shocks	Twin tube gas charged shocks

### TIRES / WHEELS

Front Tires / Rear Tires	XPS Trail King 28 x 9 / 11 x 14 in. (71.1 x 22.9 / 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum

# **BRAKES**

Front / Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers

#### **DIMENSIONS / CAPACITIES**

DIMENSIONS / GALASTILES	
Estimated Dry Weight *	1,930 lb (875.4 kg)
Chassis / Cage	Profiled cage. ROPS approved
LxWxH	160.4 x 64 x 76.2 in (407.4 x 162.6 x 193.5 cm)
Wheelbase	120.6 in. (306.3 cm)
Ground Clearance	13 in (33 cm)
Cargo Box Dimension	29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)
Cargo Box Capacity	600 lb (272.2 kg)
Towing Capacity	2,000 lb (907.2 kg)
Payload Capacity	1,280 lb (580.6 kg)
Storage Capacity	Total: 8.5 gal (32.1 L)
Fuel Capacity	10 gal (38 L)

## FEATURES

Gauge	7.6 in. (19.3 cm) wide digital display with keypad
Instrumentation	DC outlet (10-A)
Ingnition	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Magneto	650-W
Lighting	Front lighting output 110 W LED signature LED tail lights
Winch	4,500 lb (2,041 kg) winch with roller fairlead
Steering Wheel	Adjustable tilt steering
Protection	Full roof Premium half doors Full skid plate Mudguards XT front bumper
Hitch Type	2-in hitch receiver

#### WARRANTY & EXTENDED SERVICE

Factory warranty	2-year BRP limited warranty	







# **MY24 COMMANDER MAX XT-P 1000R**



#### **HIGHLIGHTS**

- Smart-Lok\* front differential
- FOX† 2.5 PODIUM QS3 Piggyback Shocks
- · Special edition seats
- 7.6 in. (19.3 cm) digital display with keypad
- LED headlights & Can-Am LED signature
- 64 in. (162.6 cm) wide with Arched A-arm
- 30 in. (76.2 cm) XPS Hammer Force tires
- 15 in. (38.1 cm) cast-aluminum beadlock wheels
- XT front bumper 4,500-lb (2,041 kg) winch
- Full roof & panoramic mirror

ENGINE	
Туре	75 kW (100 hp), Rotax® 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection
Drive Train	Selectable Turf Mode / 2WD / 4WD TRAIL / 4WD TRAIL ACTIV with exclusive Smart-Lol* * technology. * Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry
Driving Assistance	Electronic Hill Descent Control SPORT / ECO™ modes
Power Steering	Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Arched double A-arm with sway bar / 14 in. (35.6 cm) travel
Front Shocks	FOX† 2.5 PODIUM Piggyback with QS3† compression adjustment
Rear Suspension	Arched TTA with sway bar / 14 in. (35.6 cm) travel
Rear Shocks	FOX† 2.5 PODIUM Piggyback with QS3† compression adjustment
TIRES / WHEELS	
Front Tires / Rear Tires	XPS Hammer Force 30 x 10 x 15 in. (76.2 x 25.4 x 38.1 cm)
Wheels	15 in. (38.1 cm) cast-aluminum beadlock
BRAKES	
Front / Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers

### **DIMENSIONS / CAPACITIES**

DIVILITOIONO / O/II /IOTTILO	
Estimated Dry Weight *	2,000 lb (907.2 kg)
Chassis / Cage	Profiled cage. ROPS approved
LxWxH	160.4 x 64 x 76.7 in (407.4 x 162.6 x 194.8 cm)
Wheelbase	120.6 in. (306.3 cm)
Ground Clearance	13.5 in (34.3 cm)
Cargo Box Dimension	29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)
Cargo Box Capacity	600 lb (272.2 kg)
Towing Capacity	2,000 lb (907.2 kg)
Payload Capacity	1,280 lb (580.6 kg)
Storage Capacity	Total: 8.5 gal (32.1 L)
Fuel Capacity	10 gal (38 L)

#### FFATURES

TEATORES	
Gauge	7.6 in. (19.3 cm) wide digital display with keypad
Instrumentation	DC outlet (10-A)
Ingnition	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Magneto	650-W
Lighting	LED headlights LED signature LED tail lights
Winch	4,500 lb (2,041 kg) winch with roller fairlead
Steering Wheel	Adjustable tilt steering
Protection	Premium half doors Full skid plate Mudguards XT front bumper Full roof
Hitch Type	2-in hitch receiver

## WARRANTY & EXTENDED SERVICE

Factory warranty	2-year BRP limited warranty







# **MY24 COMMANDER XT 1000R**



#### HIGHLIGHTS

- 64 in. (162.6 cm) wide with Arched A-arm
- 7.6 in. (19.3 cm) digital display with keypad Can-Am LED signature
- 28 in. (71.1 cm) XPS Trail King tires
- 14 in. (35.6 cm) cast-aluminum wheels
- XT front bumper
- 4,500-lb (2,041 kg) winch
- Full roof

#### **ENGINE**

Туре	75 kW (100 hp), Rotax® 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Selectable Turf Mode / 2WD / 4WD with Visco-Lok† auto-locking front differential
Driving Assistance	Electronic Hill Descent Control SPORT / ECO™ modes
Power Steering	Dynamic Power Steering (DPS)

#### SUSPENSIONS

Front Suspension	Arched double A-arm with sway bar / 15 in. (38.1 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	Arched TTA with sway bar / 15 in. (38.1 cm) travel
Rear Shocks	Twin tube gas charged shocks

### TIRES / WHEELS

Front Tires / Rear Tires	XPS Trail King 28 x 9 / 11 x 14 in. (71.1 x 22.9 / 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum

#### **BRAKES**

Front / Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers

#### **DIMENSIONS / CAPACITIES**

Estimated Dry Weight *	1,675 lb (759.8 kg)
Chassis / Cage	Profiled cage. ROPS approved
LxWxH	130 x 64 x 74 in. (330.2 x 162.6 x 188 cm)
Wheelbase	90.6 in. (230.1 cm)
Ground Clearance	13 in (33 cm)
Cargo Box Dimension	29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)
Cargo Box Capacity	600 lb (272.2 kg)
Towing Capacity	2,000 lb (907.2 kg)
Payload Capacity	1,030 lb (467.2 kg)
Storage Capacity	Total: 7.3 gal (27.6 L)
Fuel Capacity	10 gal (38 L)

#### **FEATURES**

Gauge	7.6 in. (19.3 cm) wide digital display with keypad
Instrumentation	DC outlet (10-A)
Ingnition	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Magneto	650-W
Lighting	Front lighting output 110 W LED signature LED tail lights
Winch	4,500 lb (2,041 kg) winch with roller fairlead
Steering Wheel	Adjustable tilt steering
Protection	Premium half doors Full skid plate Mudguards XT front bumper Full roof
Hitch Type	2-in hitch receiver

## WARRANTY & EXTENDED SERVICE

Factory warranty	2-year BRP limited warranty





