TRAXTER PRO XU HD10 T ABS



Tundra Green **Timeless Black**

| ENGINE | HD10 |
|----------------------|---|
| Туре | 61 kW (82 hp) / 69 lb-ft, Rotax® 976 cc, V-twin, liquid cooled |
| Fuel Delivery System | Intelligent Throttle Control (iTC [™]) with Electronic Fuel Injection (EFI |
| Transmission | PRO-TORQ CVT Transmission with Quick Response System (QRS), high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P |
| Drive Train | Selectable Turf Mode / 2WD / 4WD with Open front differential with ABS system |
| Driving Assistance | Electronic Hill Descent Control ECO™ / ECO™ Off / Work modes Brake holding mechanism |
| Power Steering | Dynamic Power Steering (DPS) |
| Speed Category | More than 60 km/h |

SUSPENSIONS

| Front Suspension | Arched double A-arm / 11 in. (27.9 cm) travel |
|------------------|---|
| Front Shocks | Twin tube gas charged shocks |
| Rear Suspension | Arched TTA with external sway bar / 11 in. (27.9 cm) travel |
| Rear Shocks | Twin tube gas charged shocks |
| | |

TIRES

| Front Tires / Rear Tires | Maxxis Coronado† 27 x 9 / 11 x 14 in. (68.6 x 22.9 / 27.9 x 35.6 cm) |
|-----------------------------|--|
| Wheels | 14 in. (35.6 cm) cast-aluminum |
| | |
| BRAKES | |
| Front | Dual 220 mm disc brakes with hydraulic twin-piston calipers |
| Rear | Dual 220 mm disc brakes with hydraulic twin-piston calipers |
| | |

| Front | Dual 220 mm disc brakes with hydraulic twin-piston calipers |
|-------|---|
| Rear | Dual 220 mm disc brakes with hydraulic twin-piston calipers |
| | |

HIGHLIGHTS

- Dynamic Power Steering (DPS)
- Anti-Lock Braking System (ABS)

14 in. (35.6 cm) cast-aluminum wheels
27 in. (68.6 cm) Maxxis Coronado† tires

4,500-lb (2,041 kg) winch
 RF Digitally Encoded Security System (D.E.S.S.™)

· Heater-ready

| Cage | Profiled cage. ROPS approved |
|-------------------------|--|
| Estimated Dry Weight* | 1,964 lb (891 kg) |
| LxWxH | 154.1 x 64 x 78 (391.5 x 162.5 x 198.1 cm) |
| Wheelbase | 115.5 in. (294 cm) |
| Ground Clearance | 12.5 in. (32 cm) |
| Cargo Box Dimensions | 72 x 54.5 x 10 in. (180.3 x 138.4 x 25.4 cm) |
| Cargo Box Capacity | 1,200 lb (544 kg) |
| Power tilt bed | N/A |
| Tailgate Load Capacity | 250 lb (113.4 kg) |
| Storage Capacity | Total: 94 gal (356 L) |
| Towing Capacity | 2,500 lb (1136 kg) |
| Payload Capacity | 1700 lb (771 kg) |
| Fuel Capacity | 10.6 gal (40 L) |
| Person Capacity | 3 |
| FEATURES Gauge | 7.6 in. (19.3 cm) wide digital display with keypad |
| Battery | 12-V (30 amp/h) |
| Magneto | 650-W |
| Instrumentation | DC outlet (10-A) |
| Lighting | Front lighting output 140 W LED tail lights |
| Winch | 4,500-lb (2,041 kg) winch with roller fairlead |
| Seat | VERSA-PRO bench seat with passenger seats flipping up, underside hooks, reinforced seat skin |
| Steering Wheel | Adjustable tilt steering |
| Protection | Integrated front steel bumper HMWPE full skid plate Front fender extension |
| Anti-Theft System | RF Digitally Encoded Security System |
| Hitch Type | 2-in hitch receiver with rear hitch, tow ball and trailer connexion |
| | |

WARRANTY

2-year BRP limited warranty Factory warranty



A BRP BRAND

REQUEST A QUOTE



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, [®] and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. ‡Visco-Lok is a trademark of GKN Viscodrive GmbH. 1All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designed for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

TRAXTER PRO XU HD10 T ABS



Tundra Green **Timeless Black**

| MOTOR | HD10 |
|--------------------------|---|
| Tip | 61 kW (82 hp) / 69 lb-ft, Rotax® 976 cc, V-twin, sıvı soğutmalı |
| Yakıt Dağıtım Sistemi | Elektronik Yakıtlı Akıllı Gaz Kelebeği Kontrolü (i TC™) Enjeksiyon (EFI) |
| Aktarma | Hızlı Tepsi Sistemi PRO-TORQ CVT Şanzıman (QRS), Yüksek hava akışı havalandırması ve Elektronik Tahrik Kayışı Extra L / H / N / R / P |
| Güç Aktarımı | ABS Sistemli, Açık ön diferansiyelli, Seçilebilir Çim Modu / 2WD / 4WD |
| Sürüş Asistanı | Elektronik İniş Sistemi ECO''' / ECO''' Kapalı / Çalışma Modları Fren tutam mekanizması |
| Hidrolik Dreksiyon | Dinamik Servo Direksiyon (DPS™) |
| Hız Kategorisi | 60 km/h saatten fazla |


SÜSPANSİYONLAR

| Ön Süspansiyon | Kemerli Çift A Kolu 11 inç. (27,9 cm) hareket mesafesi |
|----------------------------------|--|
| Ön Şoklar | İkiz tüplü şarjlı şoklar |
| Arka Süspansiyon | Harici sallanma şubuğuna sahip Kemerli TTA / 11inç. |
| | (27,9cm)hareket mesafesi |
| Arka Şoklar | Çift tüplü gaz şarjlı şoklar |
| LASTİKLER / TEKI | ERLEKLER |
| Ön Lastikler / Arka Lastikler | Maxxis Coronado† 27 x 9 / 11 x 14 in. (68.6 x 22.9 / 27.9 x 35.6 cm) |
| Tekerlekler | 14 inç. (35,6 cm) dökme alüminyum |
| FRENLER | |
| Ön | Hidrolik çift pistonlu kaliberlere sahip çift 220 mm disk frenler |
| Arka | Hidrolik çift pistonlu kaliberlere sahip çift 220 mm disk frenler |

ÖNE ÇIKAN ÖZELLİKLER

- · Dinamik Servo Direksiyon (DPS)
- Kilitlenmeyi Önleyici Fren Sistemi (ABS)
- · 14 inç (35,6 cm) dökme alüminyum tekerlekler
- 27 inç (68,6 cm) Maxxis Coronado† lastikler
- 4,500-lb (2,041 kg) vinç
- RF Dijital Kodlu Güvenlik Sistemi (D.E.S.S.™)
- Isıtıcıya hazır

BOYUTLAR / KAPASİTELER Kafes Profilli kafes ROPS onaylı Tahmini Kuru 1.964 lb (891 kg) Ağırlık * 154.1 x 64 x 78 (391,5 x 162.5 x 198.1 cm) Ux G x Y Dingil Açıklığı 115.5 inç (294 cm) Yerden Yükseklik 12.5 inc (32 cm) Kargo Kutusu 72 x 54.5 x 10 inç. Boyutları (180,3 x 138.4 x 25.4 cm) Kargo Kutusu 1,200 lb (544 kg) Kapasitesi Güç Eğimli Yatak N/A Bagaj Kapağı 250 lb (113.4 kg) Yük Kapasitesi Depolama Kapasitesi Toplam 94 galon (356 L) 2,500 lb (1136 kg) Çekme Kapasitesi Yük Kapasitesi 1,700 lb (771 kg) Yakıt Kapasitesi 10.6 gal (40 L) Kişi Kapasitesi 3 ÖZELLİKLER Ölçü 7.6 inç (19.3 cm) genişliğinde tuş takımlı dijital ekran Akü 12-V (30 amp/h) 650-W Şarj Dinamosu Enstrümantasyon DC çıkışı (10-A) Aydınlatma Ön aydınlatma çıkışı 140 W LED arka lambalar Makaralı 4,500-lb (2,041 kg) vinç Vinç Yukarıya doğru kaldırılabilen yolcu koltukları,alt tarafta kancaları ve Koltuk güçlendirilmiş koltuk kaplaması olan VERSA-PRO koltuk sırası Direksiyon Ayarlanabilir eğimli direksiyon Entegre ön çelik tampon Koruma HMWPE tam koruma plakası Ön çamurluk uzatması Hırsızlık Önmeleme RF Dijital Kodlu Güvenlik Sistemi Sistemi Bağlantı Tipi Arka askı, çeki topuzu ve römork bağlantısına sahip 2 inç askı alıcısı T-Cat Özellikleri Korna flaşörler ve pozisyon lambaları,yan aynalar,plaka desteği, ön metal tamponda kanca





BRP -Lynx-Ski Doo / T.C. Kamu Temsilcisi

A BRP BRAND



Web Adres E-Posta

Telefon

: www.aremlojistik.com

- : emrearslan@aremlojistik.com info@aremlojistik.com
- : +90 212 602 AREM



MY24 TRAXTER XU HD9 T ABS



HIGHLIGHTS

• Dynamic Power Steering (DPS)

- Anti-Lock Braking System (ABS)
- 14 in. (35.6 cm) cast-aluminum wheels
- 27 in. (68.6 cm) Maxxis Coronado† tires
- 4,500-lb (2,041 kg) winch

DIMENSIONS / CADACITIES

- RF Digitally Encoded Security System (D.E.S.S.™)
- Heater-ready

Stone Gray

ENGINES

| Туре | 48 kW (65 hp) / 59 lb-ft , Rotax [®] 976 cc, V-twin, liquid cooled |
|----------------------|--|
| Fuel Delivery System | Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI) |
| Transmission | PRO-TORQ CVT with Quick Response System (QRS), high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P |
| Drive Train | Selectable Turf Mode / 2WD / 4WD with Open front differential with ABS system |
| Driving Assistance | Electronic Hill Descent Control ECO™ / ECO™ Off / Work modes Brake holding mechanism |
| Power Steering | Dynamic Power Steering (DPS) |
| Speed Category | More than 60 km/h |

SUSPENSIONS

| Front Suspension | Arched double A-arm / 11 in. (27.9 cm) travel |
|------------------|---|
| Front Shocks | Twin tube gas charged shocks |
| Rear Suspension | Arched TTA with external sway bar / 11 in. (27.9 cm) travel |
| Rear Shocks | Twin tube gas charged shocks |

TIRES / WHEELS

| Front Tires / Rear Tires | Maxxis Coronado† 27 x 9 / 11 x 14 in. (68.6 x 22.9 / 27.9 x 35.6 cm) |
|--------------------------|--|
| Wheels | 14 in. (35.6 cm) cast-aluminum |
| | |

BRAKES

| Front | Dual 220 mm disc brakes with hydraulic twin-piston calipers |
|-------|---|
| Rear | Dual 220 mm disc brakes with hydraulic single-piston calipers |

| Cage | Profiled cage. ROPS approved |
|------------------------|---|
| Estimated Dry Weight* | 1,572 lb (713 kg) |
| LxWxH | 125.7 x 64 x 80 in. (319.4 x 162.5 x 203.2 cm) |
| Wheelbase | 83 in. (211.5 cm) |
| Ground Clearance | 13 in. (33 cm) |
| Cargo Box Dimensions | 38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm) |
| Cargo Box Capacity | 1,000 lb (454 kg) |
| Power tilt bed | N/A |
| Tailgate Load Capacity | 250 lb (113.4 kg) |
| Storage Capacity | Total: 6.5 gal (24.5 L) |
| Towing Capacity | 2,500 lb (1136 kg) |
| Payload Capacity | 1,500 lb (680 kg) |
| Fuel Capacity | 10.6 gal (40 L) |
| Person Capacity | 3 |
| FEATURES Gauge | 7.6 in. (19.3 cm) wide digital display with keypad |
| Battery | 12-V (30 amp/h) |
| Magneto | 650-W |
| Instrumentation | DC outlet (10-A) |
| Lighting | Front lighting output 140 W LED tail lights with halo glow effect |
| Winch | 4,500-lb (2,041 kg) winch with roller fairlead |
| Seat | VERSA-PRO bench seat with passenger seats flipping up, underside hooks, reinforced seat skin |
| Steering Wheel | Adjustable tilt steering |
| Protection | Integrated front steel bumper HMWPE full skid plate Front Fender Extension |
| Anti-Theft System | RF Digitally Encoded Security System |
| | 2-in hitch receiver with rear hitch, tow ball and trailer connexion |
| Hitch Type | |

WARRANTY

Factory warranty 2-year BRP limited warranty





REQUEST A QUOTE



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, * and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. ‡Visco-Lok is a trademark of GKN Viscodrive GmbH. 1All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

MY24 TRAXTER XU HD10 T ABS



Timeless Black

ENGINE

| Туре | 61 kW (82 hp) / 69 lb-ft, Rotax® 976 cc, V-twin, liquid cooled |
|----------------------|---|
| Fuel Delivery System | Intelligent Throttle Control (iTC [™]) with Electronic Fuel Injection (EFI) |
| Transmission | PRO-TORQ CVT Transmission with Quick Response System (QRS), high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P |
| Drive Train | Selectable Turf Mode / 2WD / 4WD with Open front differential with ABS system |
| Driving Assistance | Electronic Hill Descent Control ECO™ / ECO™ Off / Work modes Brake holding mechanism |
| Power Steering | Dynamic Power Steering (DPS™) |
| Speed Category | More than 60 km/h |
| SUSPENSIONS | |

| Front Suspension | Arched double A-arm / 11 in. (27.9 cm) travel |
|------------------|---|
| Front Shocks | Twin tube gas charged shocks |
| Rear Suspension | Arched TTA with external sway bar / 11 in. (27.9 cm) travel |
| Rear Shocks | Twin tube gas charged shocks |

TIRES / WHEELS

| Front Tires / Rear Tires | Maxxis Coronado† 27 x 9 / 11 x 14 in. (68.6 x 22.9 / 27.9 x 35.6 cm) |
|-----------------------------|--|
| Wheels | 14 in. (35.6 cm) cast-aluminum |
| BRAKES | |

| DRAKES | |
|--------|--|
| Front | Dual 220 mm disc brakes with hydraulic twin-piston calipers |
| Rear | Dual 220 mm disc brakes with hydraulic single-piston calipers |

HIGHLIGHTS

- Dynamic Power Steering (DPS)
- Anti-Lock Braking System (ABS)
 14 in. (35.6 cm) cast-aluminum wheels
- 27 in. (68.6 cm) Maxxis Coronado† tires 4,500-lb (2,041 kg) winch
- RF Digitally Encoded Security System (D.E.S.S.™)
- · Heater-ready

DIMENSIONS / CAPACITIES

| Cage | Profiled cage. ROPS approved |
|---------------------------|--|
| Estimated Dry Weight * | 1,594 lb (723 kg) |
| LxWxH | 125.7 x 64 x 80 in. (319.4 x 162.5 x 203.2 cm) |
| Wheelbase | 83 in. (211.5 cm) |
| Ground Clearance | 13 in. (33 cm) |
| Cargo Box Dimensions | 38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm) |
| Cargo Box Capacity | 1,000 lb (454 kg) |
| Power tilt bed | N/A |
| Tailgate Load Capacity | 250 lb (113.4 kg) |
| Storage Capacity | Total: 6.5 gal (24.5 L) |
| Towing Capacity | 2,500 lb (1136 kg) |
| Payload Capacity | 1,500 lb (680 kg) |
| Fuel Capacity | 10.6 gal (40 L) |
| Person Capacity | 3 |

FEATURES

| Gauge | 7.6 in. (19.3 cm) wide digital display with keypad |
|-------------------|---|
| Battery | 12-V (30 amp/h) |
| Magneto | 650-W |
| Instrumentation | DC outlet (10-A) |
| Lighting | Front lighting output 140 W LED tail lights with halo glow effect |
| Winch | 4,500-lb (2,041 kg) winch with roller fairlead |
| Seat | VERSA-PRO bench seat with passenger seats flipping up, underside hooks, reinforced seat skin |
| Steering Wheel | Adjustable tilt steering |
| Protection | Integrated front steel bumper HMWPE full skid plate Front fender extension |
| Anti-Theft System | RF Digitally Encoded Security System |
| Hitch Type | 2-in hitch receiver with rear hitch, tow ball and trailer connexion |
| T-Cat Features | Horn, flashers and position lamps, side mirrors, license plate support, hook on front metal bumper |
| | |

WARRANTY

2-year BRP limited warranty Factory warranty





REQUEST A QUOTE



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, [®] and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. ‡Visco-Lok is a trademark of GKN Viscodrive GmbH. 1All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designed for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.