



Mountain / Deep Snow + Steep ja deep + On & Off Trail + Utility

| ROTAX® ENGINE | 600R E-TEC | 850 E-TEC |
|------------------------------|------------------------------------------------|---------------------------------------------------------------------|
| Engine details | Liquid-cooled, two-stroke, 3-D R.A.V.E.™ | Liquid-cooled, two-stroke, 3-D R.A.V.E.™ |
| Cylinders | | 2 |
| Displacement | 599.4 cc | 849 cc |
| Bore | 72.3 mm | 82 mm |
| Stroke | 73 mm | 80.4 mm |
| Maximum engine speed | 8100 RPM | 7900 RPM |
| Carburation | Electronic Direct Injection | Electronic Direct Injection with additional booster injectors |
| Recommended fuel type | Unle | eaded |
| Minimum octane | Ş | 95 |
| Fuel tank | 37 liters | |
| Oil tank capacity (2-stroke) | 3.4 liters | |
| | | |

| COLOUR | Orange/Full Moon Silver/Black |
|-------------------------|----------------------------------|
| DIMENSIONS | |
| Vehicle overall length* | 3385 mm |
| Vehicle overall width | 1120 mm |
| Vehicle overall height | 1320 mm |
| Ski stance | 921 mm |
| Track nominal width | 381 mm |
| Track nominal length | 3923 mm |
| Track profile height | 64 mm PowderMax |

POWERTRAIN

| Drive clutch type | pDrive wi | th clickers |
|--------------------|---------------------------------------------------------------------------|-------------|
| Driven clutch type | Q | RS |
| Brake system | Hydraulic brake with braided steel brake line, plastic master cylinder | |
| DRY WEIGHT | | |
| Dry weight | 240 kg | 249 kg |

SUSPENSION

| LFS with bended lower A-Arms |
|------------------------------------|
| KYB 36 |
| PPS ² -DS+ |
| KYB 36 |
| KYB 36 |
| |

FEATURES

| Frame | Radien² |
|-----------------------|---------------------------------------------|
| Skis | Blade DS+ |
| Seating | Sport, 1-up |
| Handlebar | U-type steel with hooks, low grab handle |
| Riser block height | 145 mm |
| Starter | Electric and manual |
| Reverse | RER |
| Heated throttle lever | Standard |
| | |

| Heated grips | Standard 7.2-in. wide digital display | |
|-------------------------|---------------------------------------|--|
| Gauge | | |
| Windshield | Medium with side deflectors | |
| Hitch | Standard | |
| Visor Plug front / rear | Front | |
| USB power outlet | Yes, in front compartment | |
| Air radiator with fan | Yes | |
| LinQ attachment | Multi-LinQ plate | |
| | | |



^{*} Vehicle overall length without snowflap.



| ROTAX® ENGINE | 600 ACE | |
|-----------------------|-------------------------------------|--|
| Engine details | Liquid-cooled, four-stroke D.O.H.C. | |
| Cylinders | 2 | |
| Displacement | 600 cc | |
| Bore | 74 mm | |
| Stroke | 69.7 mm | |
| Maximum engine speed | 7250 RPM | |
| Carburation | EFI | |
| Recommended fuel type | Unleaded | |
| Minimum octane | 95 | |
| Fuel tank | 37 liters | |

| COLOUR | Silver/Black |
|-------------------------|--------------|
| DIMENSIONS | |
| Vehicle overall length* | 3290 mm |
| Vehicle overall width | 1200 mm |
| Vehicle overall height | 1540 mm |
| Ski stance | 996 mm |
| Track nominal width | 406 mm |
| Track nominal length | 3923 mm |
| Track profile height | 38 mm DSG |
| | |

+ Utility

POWERTRAIN

| Drive clutch type | eDrive II | |
|--------------------|---------------------------------------------------------------------------|--|
| Driven clutch type | QRS | |
| Brake system | Hydraulic brake with braided steel brake line, plastic master cylinder | |
| | | |

DRY WEIGHT

Dry weight 246 kg

SUSPENSION

| Front suspension | LFS+ with bended lower A-Arms |
|------------------|-------------------------------------|
| Front shock | KYB 36 |
| Rear suspension | EasyRide |
| Center shock | KYB 36 |
| Rear shock | KYB 36 |

FEATURES

| Frame | Radien-X |
|-----------------------|---------------------------------------------|
| Skis | Blade DS+ |
| Seating | 2-up light |
| Handlebar | U-type steel with hooks, low grab handle |
| Riser block height | 145 mm |
| Starter | Electric |
| Reverse | Mechanical |
| Heated throttle lever | Standard |

| Heated grips | Standard | |
|-------------------------|---------------------------------|--|
| Gauge | 4.5-in. digital display | |
| Windshield | Extra high with side deflectors | |
| Hitch | Standard | |
| Visor Plug front / rear | Front | |
| USB power outlet | Yes, in front compartment | |
| Air radiator with fan | Yes | |
| LinQ attachment | Multi-LinQ plate | |



^{*} Vehicle overall length without snowflap.



| ROTAX® ENGINE | 900 ACE | 900 ACE Turbo |
|-----------------------|-------------------------------------------|---------------------------------------------------------|
| Engine details | Liquid-cooled, four-stroke D.O.H.C. | Liquid-cooled, four-stroke D.O.H.C., turbocharged |
| Cylinders | 3 | |
| Displacement | 899.0 cc | |
| Bore | 74 mm | |
| Stroke | 69.7 mm | |
| Maximum engine speed | 7250 RPM | 7750 RPM |
| Carburation | EFI | |
| Recommended fuel type | Unleaded | |
| Minimum octane | 95 | |
| Fuel tank | 37 liters | |

| COLOUR | Noble Bronze / Black | |
|-------------------------|----------------------|--|
| DIMENSIONS | | |
| Vehicle overall length* | 3290 mm | |
| Vehicle overall width | 1280 mm | |
| Vehicle overall height | 1470 mm | |
| Ski stance | 1097 mm | |
| Track nominal width | 406 mm | |
| Track nominal length | 3923 mm | |
| Track profile height | 51 mm PowderMax | |

POWERTRAIN

| Drive clutch type | pDrive with slider shoes (900 ACE) pDrive (900 ACE Turbo) |
|--------------------|---------------------------------------------------------------------------|
| Driven clutch type | QRS |
| Brake system | Hydraulic brake with braided steel brake line, plastic master cylinder |

SUSPENSION

| Front suspension | ion LFS+ | |
|------------------|--------------------------|--|
| Front shock | KYB 36 | |
| Rear suspension | EasyRide with adjustment | |
| Center shock | KYB 36 | |
| Rear shock | KYB 36 | |

DRY WEIGHT

| Dry weight | 262 kg | 274 kg |
|------------|--------|--------|

FEATURES

| Frame | Radien-X | |
|-----------------------|---------------------------------------------|--|
| Skis | Blade DS+ | |
| Seating | 2-up | |
| Handlebar | U-type steel with hooks, low grab handle | |
| Riser block height | 145 mm | |
| Starter | Electric | |
| Reverse | Mechanical | |
| Heated throttle lever | Standard | |

| Heated grips | Standard | |
|-------------------------|---------------------------------|--|
| Gauge | 7.2-in. wide digital display | |
| Mirrors | Standard | |
| Windshield | Extra high with side deflectors | |
| Hitch | Standard | |
| Visor Plug front / rear | Front | |
| USB power outlet | Yes, in front compartment | |
| Air radiator with fan | Yes | |
| LinQ attachment | Multi-LinQ plate | |



^{*} Vehicle overall length without snowflap.