

ROTAX® ENGINE	600R E-TEC	COLOUR
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	
Cylinders	2	DIMENSION
Displacement	599.4 cc	Vehicle overall
Bore	72.3 mm	Vehicle overall
Stroke	73 mm	Vehicle overal
Maximum engine speed	8100 RPM	Ski stance
Carburation	Electronic Direct Injection	Track nominal
Recommended fuel type	Unleaded	Track nominal
Minimum octane	95	Track profile h
Fuel tank	37 liters	
Oil tank capacity (2-stroke)	3.4 liters	

COLOUR	Bright White / Evo Red	
DIMENSIONS		
Vehicle overall length*	2920 mm	
Vehicle overall width	1270 mm	
Vehicle overall height	1140 mm	
Ski stance	1097 mm	
Track nominal width	381 mm	
Track nominal length	3269 mm	
Track profile height	41 mm Cobra	

## POWERTRAIN

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	RS brake with 4 piston caliber, adjustable brake lever, aluminium master cylinder
DRY WEIGHT	

## SUSPENSION

Front suspension	LFS+
Front shock	KYB PRO 46 HLCR Kashima
Rear suspension	PPS <sup>3</sup>
Center shock	KYB PRO 46 HLCR Kashima
Rear shock	KYB PRO 46 HLCR Kashima

## FEATURES

Dry weight

Blade XC+ Sport, 1-up	
Sport, 1-up	
Sport, 1-up	
U-type aluminium with hooks	
90 mm	
Manual	
RER	

Heated throttle lever Standard		
Heated grips	Standard	
Gauge	7.2-in. wide digital display	
Windshield	Extra low	
USB power outlet	Yes, in front compartment	
LinQ attachment	1 pair	

\* Vehicle overall length without snowflap.

©2023 Bombardier Recreational Products Inc., (BRP). All rights reserved. <sup>™</sup>,\* and the BRP logo are trademarks of BRP or its affiliates. †All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.

219 kg





ROTAX® ENGINE	600R E-TEC	850 E-TEC	COLOUR	
Engine details	Liquid-cooled, two	o-stroke, 3-D R.A.V.E.™		
Cylinders		2	DIMENSIONS	
Displacement	599.4 cc	849 cc	Vehicle overall length*	
Bore	72.3 mm	82 mm	Vehicle overall width	
Stroke	73 mm	80.4 mm	Vehicle overall height	
Maximum engine speed	8100 RPM	7900 RPM	Ski stance	
Carburation	Electronic Direct	Electronic Direct	Track nominal width	
	Injection	Injection with additional booster injectors	Track nominal length	
Recommended fuel type	Un	leaded	Track profile height	4 32 m
Minimum octane		95	flack prome neight	studo
Fuel tank	37	' liters		
Oil tank capacity (2-stroke)	3.4 liters			

DIMENSIONS	
Vehicle overall length*	3040 mm
Vehicle overall width	1270 mm
Vehicle overall height	1140 mm
Ski stance	1097 mm
Track nominal width	381 mm
Track nominal length	3487 mm
Track profile height	41 mm Cobra 32 mm Ice Ripper XT studded (spring only)

Platinum Silver Satin / Evo Red

POWERTRAIN	
Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	RS brake with 4 piston caliber, adjustable brake lever, aluminium master cylinder
DRY WEIGHT	

220 kg

SUSPENSION	
Front suspension	LFS+
Front shock	KYB PRO 46 HLCR Kashima
Rear suspension	PPS <sup>3</sup>
Center shock	KYB PRO 46 HLCR Kashima
Rear shock	KYB PRO 46 HLCR Kashima

## **FEATURES**

Dry weight

Frame	Radien <sup>2</sup>	Heated throttle lever	Standard
Skis	Blade XC+	Heated grips	Standard
Seating	Sport, 1-up	Gauge	7.2-in. wide digital display /
Handlebar	U-type aluminium with hooks		10.25-in Color Display (spring only)
Riser block height	90 mm	Windshield	Extra low
Starter	Manual Electric (spring only)	USB power outlet	Yes, in front compartment
Reverse	RER	LinQ attachment	2 pairs

228 kg

\* Vehicle overall length without snowflap.

©2023 Bombardier Recreational Products Inc., (BRP). All rights reserved. ™,\* and the BRP logo are trademarks of BRP or its affiliates. †All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.

