

A supreme travel powerhouse with segment-leading features and exhilarating performance, for adrenaline-seekers who are after the most extreme high speed adventures. 

DARE TO RACE ANYWHERE

ADVENTURE BEYOND



KTM 1290 SUPER ADVENTURE S

The S model sets a new benchmark in performance-enhancing technology. It is the sportiest Adventure bike on the street and impresses with agility, performance, long-distance comfort and the most advanced electronics.

HIGHLIGHT FEATURES

- > ALL-NEW ERGONOMICS OFFERING ADDED AGILITY
- > VARIABLE AND LOWER SEAT HEIGHT
- > NEW GENERATION OF SEMI-ACTIVE SUSPENSION
- > OPTIMIZED WEIGHT DISTRIBUTION WITH NEW FUEL TANKS
- > INNOVATIVE ADAPTIVE CRUISE CONTROL AS STANDARD
- > CUTTING-EDGE ELECTRONICS ENHANCING EVERY RIDE
- > INTUITIVE 7" TFT DISPLAY
- > REVISED LC8 ENGINE [EURO 5]
- > REMODELED OPTIONAL SOFTWARE PACKAGES
- > STANDARD SOFTWARE FEATURES:











KTM 1290 SUPER ADVENTURE S



KTM 1290 SUPER ADVENTURE R



KTM 890 ADVENTURE

ENGINE (LIQUID COOLED)				
ENGINE TYPE	2-cylinder, 4-stroke, V 75°	2-cylinder, 4-stroke, V 75°	2 cylinders, 4 stroke, Parallel twin	
DISPLACEMENT	1,301 cc	1,301 cc	899 cc	
BORE X STROKE	108 mm x 71 mm	108 mm x 71 mm	90.7 mm x 68.8 mm	
POWER OUTPUT	118 kW (160 hp) @ 9,000 rpm	118 kW (160 hp) @ 9,000 rpm	77 kW (105 hp) @ 8,000 rpm	
MAX. TORQUE	138 Nm @ 6,500 rpm	138 Nm @ 6,500 rpm	100 Nm @ 6,500 rpm	
FUEL CONSUMPTION	5.7 liters/100 km	5.7 liters/100 km	4.5 liters/100 km	

TRANSMISSION

CLUTCH	PASC slipper clutch, hydraulically operated	PASC slipper clutch, hydraulically operated	Cable operated PASC Slipper clutch	CLUTCH	Cable operated PASC Slipper clutch	Cable operated PASC Slipper clutch	Cable operated PASC Slipper clutch
GEARBOX	6 gears	6 gears	6 gears	GEARBOX	6 gears	6 gears	6 gears
FINAL DRIVE	17:42/X-Ring chain	17:42/X-Ring chain	16:45/X-Ring chain	FINAL DRIVE	16:45/X-Ring chain	16:45/X-Ring chain	15:45/X-Ring chain

ELECTRONICS

ENGINE MANAGEMENT	Keihin EMS with RBW and ACC, double ignition	Keihin EMS with RBW and cruise control, double ignition	Bosch EMS with RBW	_	ENGINE MANAGEMENT	Bosch EMS with RBW	Bosch EMS with RBW	Bosch EMS with RBW
TRACTION CONTROL (disengageable)	MTC (lean-angle sensitive, 4-mode)	MTC (lean-angle sensitive, 4-mode)	MTC (lean angle sensitive, 3-mode, Rally Mode optional)	_	TRACTION CONTROL (disengageable)	MTC (lean-angle sensitive, 3-mode)	MTC (lean angle sensitive, 3-mode + Rally)	MTC (lean angle sensitive)
ABS (disengageable)	Bosch 10.3ME Combined-ABS (incl. Cornering ABS & Offroad	d Mode) Bosch 10.3ME Combined-ABS (incl. Cornering ABS & Offroad M	lode) Bosch 9.1MP (incl. Cornering-ABS & Offroad Mode)		ABS (disengageable)	Bosch 9.1 MP (incl. Cornering-ABS & Offroad Mode)	Bosch 9.1 MP (incl. Cornering ABS & Offroad Mode)	Bosch 9.1MP (incl. Cornering-ABS & Offroad Mode)

CHASSIS & BRAKES

FRAME	Chromium-Molybdenum-Steel trellis frame, powder coated	Chromium-Molybdenum-Steel trellis frame, powder coated	Chromium-Molybdenum-Steel frame, powder coated
SUBFRAME	Aluminum, powder coated	Aluminum, powder coated	Chromium-Molybdenum-Steel trellis, powder coated
HANDLEBAR	Aluminum, tapered, Ø 28/22 mm	Aluminum, tapered, Ø 28/22 mm	Aluminum, tapered, Ø 28/22 mm
FRONT SUSPENSION/ADJUSTABILITY	WP SAT (semi-active technology) Upside-Down Ø 48 mm/Semi-active	WP XPLOR Upside-Down Ø 48 mm/Compression, rebound, preload	WP APEX Upside-Down Ø 43 mm
REAR SUSPENSION/ADJUSTABILITY	WP SAT (semi-active technology) shock absorber/Semi-active	WP XPLOR shock absorber with PDS/Compression, rebound, preload	WP APEX shock absorber/Preload and rebound
SUSPENSION TRAVEL FRONT/REAR	200 mm/200 mm	220 mm/220 mm	200 mm/200 mm
WHEELBASE	1,557 mm ± 15 mm	1,577 mm ± 15 mm	1,509 mm ± 15 mm
WHEELS FRONT/REAR	Cast aluminum wheels 3.50 x 19"; 5.00 x 17"	Forged aluminum rims with spokes 2.5 x 21" ; 4.25 x 18"	Spoked wheels with aluminum rims, 2.50 x 21"; 4.50 x 18"
TIRES FRONT/REAR	120/70 ZR 19"; 170/60 ZR 17"	90/90 21"; 150/70 ZR 18"	90/90-21"; 150/70-18"
FRONT BRAKE	2 x Brembo 4-piston, radially mounted caliper, brake disc Ø 320 mm	2 x Brembo 4-piston, radially mounted caliper, brake disc Ø 320 mm	2 x radially mounted 4 piston caliper, brake disc Ø 320 mm
REAR BRAKE	Brembo 2-piston, fixed caliper, brake disc Ø 267 mm	Brembo 2-piston, fixed caliper, brake disc Ø 267 mm	2 piston floating caliper, brake disc Ø 260 mm

DIMENSIONS & WEIGHT

SEAT HEIGHT/GROUND CLEARANCE	849-869 mm/223 mm	880 mm/242 mm	830 mm-850 mm/233 mm	SEAT HEIGHT/GROUND CLEARANCE	880 mm/263 mm	910 mm/303 mm	855 mm/200 mm
TANKS CAPACITY/RESERVE	approx. 23 liters/5 liters reserve	approx. 23 liters/5 liters reserve	approx. 20 liters/3 liters reserve	TANKS CAPACITY/RESERVE	approx. 20 liters/3 liters reserve	approx. 20 liters/3 liters reserve	approx. 14.5 liters/3.5 liters reserve
DRY WEIGHT	approx. 220 kg	approx. 221 kg	approx. 196 kg	DRY WEIGHT	approx. 196 kg	approx. 196 kg	approx. 158 kg



ELECTRONICS

CHASSIS & BRAKES

FRAME SUBFRAME HANDLEBAR FRONT SUSPEN REAR SUSPENSI SUSPENSION TR WHEELBASE WHEELS FRONT TIRES FRONT/R FRONT BRAKE

REAR BRAKE







KTM 890 ADVENTURE R

KTM 890 ADVENTURE R RALLY

KTM 390 ADVENTURE

ENGINE (LIQUID COOLED)			
ENGINE TYPE	2 cylinders, 4 stroke, Parallel twin	2 cylinders, 4 stroke, Parallel twin	Single-cylinder, 4 stroke
DISPLACEMENT	889 cc	889 cc	373.2 cc
BORE X STROKE	90.7 mm x 68.8 mm	90.7 mm x 68.8 mm	89 mm x 60 mm
POWER OUTPUT	77 kW (105 hp) @ 8,000 rpm	77 kW (105 hp) @ 8,000 rpm	32 kW (44 hp) @ 9,000 rpm
MAX. TORQUE	100 Nm @ 6,500 rpm	100 Nm @ 6,500 rpm	37 Nm @ 7,000 rpm
FUEL CONSUMPTION	4.5 liters/100 km	4.5 liters/100 km	3.37 liters/100 km

TRANSMISSION

	Chromium-Molybdenum-Steel frame, powder coated	Chromium-Molybdenum-Steel frame, powder coated	Steel trellis frame, powder coated
	Chromium-Molybdenum-Steel trellis, powder coated	Chromium-Molybdenum-Steel trellis, powder coated	Bolt on steel trellis frame, powder coated
	Aluminum, tapered, Ø 28/22 mm	Aluminum, tapered, Ø 28/22 mm	Aluminum, tapered, Ø 26/22 mm
ENSION/ADJUSTABILITY	WP XPLOR Upside-Down Ø 48 mm/Compression, rebound, preload	WP XPLOR PRO 7548/Compression, rebound, preload	WP APEX Upside-Down Ø 43 mm/Compression, rebound
NSION/ADJUSTABILITY	WP XPLOR shock absorber with PDS/Compression, rebound, preload	WP XPLOR PRO 6746 shock absorber with PDS/Compression, rebound, preload	WP APEX shock absorber/Rebound, preload
TRAVEL FRONT/REAR	240 mm/240 mm	270 mm/270 mm	170 mm/177 mm
	1,528 mm ± 15 mm	1,535 mm ± 15 mm	1,430 mm ± 15 mm
NT/REAR	Spoked wheels with aluminum rims, 2.50 x 21"; 4.50 x 18"	Spoked wheels with aluminum rims, 2.15 x 21"; 4.00 x 18"	Cast aluminum wheels 2.50 x 19"; 3.50 x 17"
/REAR	90/90-21"; 150/70-18"	90/90-21"; 150/70-18"	100/90-19"; 130/80-17"
E	2 x radially mounted 4 piston caliper, brake disc Ø 320 mm	2 x radially mounted 4 piston caliper, brake disc Ø 320 mm	4-piston, radially mounted caliper, brake disc Ø 320 mm
	2 piston floating caliper, brake disc Ø 260 mm	2 piston floating caliper, brake disc Ø 260 mm	Single piston, floating caliper, brake disc Ø 230 mm

DIMENSIONS & WEIGHT



CHOOSE HIGH-PERFORMANCE ADVENTURE.

The KTM 1290 SUPER ADVENTURE S

is a sporty all-rounder that strongly emboldens the idea that 'adventure riding' is not only about dirt. With sure-footed handling, class-leading electronics, and exceptional top performance, this travel weapon is for those who enjoy carving up corners all day long on the latest high-tech machinery. Its state-of-the-art chassis and premium semi-active suspension provide the comfort and confidence adrenaline-seeking adventurers need when pushing their limits. With innovative rider aids like adaptive cruise control, this sporty Adventure bike eats up the miles at pace and leaves you with enough energy to attack when the next challenging section arrives.

